

Technical data sheet



Synthetic lubricant for plastic tubes

For sealing and mounting

Application in sanitary areas and civil engineering.

Advantages & Features

- Can be mixed with water
- Suitable for drinking water
- For all diameters
- Excellent lubrication and conductivity properties
- Skin friendly
- pH value: 8,5-9,5
- Colour: white
- Processing temperature: -5°C up to 40° C
- Consistency: pasty

Application areas

Application in the sanitary sector and in civil engineering.

Tests and Approvals

Corresponds to the guidelines of DVGW (VP461 for water supply) and approved by WRAS..

Application

Thanks to its excellent lubricating and sliding properties, the lubricant supports the assembly of the pipes and, if used correctly, prevents folds in the sealing area and thus prevents leaks. We recommend applying a sufficient amount of the lubricant immediately before installing the pipes in order to prevent the lubricating film from drying out. Can be colored according to customer requirements

Shelf life and storage:.

36 months in the originally sealed container at +5°C to +25°C.

Order-number, article and packing unit

Order-no.	Article	PU
21003	30ml tube	250
21005	150 ml angled neck tube	50
21001	250 ml bottle	9
21002	500 ml bottle	6

Notice

All information and recommendations contained in this technical data sheet do not represent guaranteed properties. They are based on our research results and experience. However, they are non-binding as we are not responsible for compliance with the processing conditions

may be, since we do not know the special application conditions at the user.

A guarantee can only be given for the consistently high quality of our products. We recommend that you conduct sufficient tests to determine whether the specified product has the properties you want. A claim from this is excluded. The processor bears sole responsibility for incorrect or inappropriate use.

Safety and health

See safety data sheet.