



**Gaskets for wall-mounted valves and fittings**  
New sealing technology for wall fittings.

### Advantages & Features

- fast and clean
- adhesive on one side
- mountable without tools
- no wall sealing with silicone
- removable
- no dirty rosette or S-connection
- approx. 64mm Ø cellular rubber
- no mold formation
- Prevents moisture from penetrating the masonry, plaster, drywall etc.

### Application areas

Can be used for the sealing of wall fittings/S bends in the sanitary area. Prevents moisture from penetrating into the masonry, plaster, dry construction, ...

### Tests and Approvals

./.

### Application

- Remove foil
- Adjust the seal to the height of the rosette if necessary
- Put the seal on the S-bow
- Mount screw rosette

### Shelf life and storage

3 years shelf life in the originally sealed container.

### Order number, article & packaging units

Order-no.	article	PU
23001	2 pack(20mm height)	18
23006	2 pack XL (height 31mm)	18

### Notice

All information and recommendations contained in this technical data sheet do not represent guaranteed properties. They are based on our research results and experience. However, they are non-binding as we are not responsible for compliance with the processing conditions may be, since we do not know the special application conditions at the user. A guarantee can only be given for the consistently high quality of our products. We recommend that you conduct sufficient tests to determine whether the specified product has the properties you want. A claim from this is excluded. The processor bears sole responsibility for incorrect or inappropriate use.

### Dimensions:

	23001:	23006:
Outer diameter:	64 mm	68 mm
Inner diameter:	24 mm	28 mm

### Safety and health

See safety data sheet

