Hemp/flax

Technical data sheet





Hemp/flax in combination with sealing paste for sealing metal pipe thread connections of all kinds in the field of plumbing and heating as well as in industrial installations.

Advantages and properties

suitable for drinking water				
temperature resistant				
pressure resistant				
stability enhancing				
Easy to process				
Temperature resistance up to 140° C (in connection with sealing paste)				
Pressure resistance: Up to 200 bar				
Form: Fibrous*				
Colour: grey-yellow*				

^{*}Hemp/flax is a natural product and can vary in colour, consistency and appearance.

Application areas

Hemp/flax improves the stability of the thread connection under pressure and, together with the sealing paste, seals the thread.

Use

Take hemp/flax in the appropriate amount from the braid or spool. Now wrap this evenly and tightly around the thread, from the end of the pipe inwards. The thread should be filled with hemp/flax so that the tips of the thread are still visible. The hemp/flax should not cover, cross or protrude into the pipe opening.

Durability and storage

Storage must be dry and at normal humidity. Storage time up to 5 years.

Order number, article & packaging units

Mazzoni-Flachs EXTRA (flax heckled and braided))

Order-no.	article	PU
24002	200g braid	62
24003	80g bobbin	10
24004	Dispenser for bobbin (80g)	15
24005	40g flax in dispenser	25
24006	80g flax in dispenser	16
24007	40g bobbin	10
24014	100g braid	125
25416	100g flax ball blistered	8

Mazzoni rein Hanf-Ersatz Spezial (hemp equivalent finely heckled and braided)

Order-no.	article	PU
25702	200g braid	62

Mazzoni-Flachs +GF+

Order-no.	article	PU
25415	80g bobbin	10

Notice

All information and recommendations contained in this technical data sheet do not represent guaranteed properties. They are based on our research results and experience. However, they are non-binding, since we cannot be responsible for compliance with the processing conditions, since we are not aware of the special application conditions at the user. A guarantee can only be given for the consistently high quality of our products. We recommend that you conduct sufficient tests to determine whether the specified product has the properties you want. A claim from this is excluded. The processor bears sole responsibility for incorrect or inappropriate use.

Safety and health

See safety data sheet

Fermit GmbH

Zur Heide 4 – D-53560 Vettelschoß Tel.: +49(0)2645 - 2207 / Fax: +49(0)2645 – 3113 Mail: <u>info@fermit.de</u> - Web: <u>www.fermit.de</u>